



TECHNICAL SPECIFICATION

Description:

Advance N333 is a flotation tyre suitable for balers, agricultural trailers, manure spreaders and heavy seed drills.

The tyre features good traction on any surface and excellent self-cleaning properties. The low soil compaction reduces the stress on the soil.



Pattern: N-333

TECHNICAL DATA:

Size	Advance Pattern	Load Index	Speed Symbol	Type	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (BAR)	Load Capacity (kgs)	Load Capacity		Tread Depth (mm)
										(km/h)	(kgs)	
560 / 45 R 22.5	N333	152	D	TL	16.00	1076	543	4.0	3550	65	3550	27
710 / 45 R 22.5	N333	165	D	TL	24.00	1212	727	4.0	5150	65	5150	27
560 / 60 R 22.5	N333	165	D	TL	16.00	1244	543	5.0	5150	65	5150	27
710 / 50 R 26.5	N333	170	D	TL	24.00	1383	727	4.0	6000	65	6000	28
600 / 55 R 26.5	N333	165	D	TL	20.00	1333	611	4.0	5150	65	5150	28

Legal Information:

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Guizhou Tyre Co., LTD. or any subsidiary or affiliated company does not undertake any responsibility or liability for undetected errors and/or misprints.

All rights reserved. The materials and contents of this publication are the exclusive property of Guizhou Tyre Co., LTD. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish any contents in whole or in part on paper format and electronic format or otherwise without prior written consent by Guizhou Tyre Co., LTD.