

320 VALUE PLUS

IMP



A 320 Value Plus is specially designed for agricultural implements. Its large footprint & high rubber to void ratio minimizes soil compaction. Strong textile construction ensures optimal performance and long tire life. This tire can be used on roads and also for grassland and sensitive soil applications in the fields.



Size	Rim Width (inch)	Unloaded Dimension		Loaded Static Radius (mm)	Rolling Circumference (mm)	PR LOAD INDEX / SPEED SYMBOL	Inflated Pressure (Bar)	Recommend load, kg (lbs)				
		SW (mm)	OD (mm)					Speed, km/h (mph)				
								Free rolling				
								Static -	10 6	25 16	30 18	40 25
7.00-12 (3 rib)	4.25X12	185	667	295	1944	6	2.5	1280	1000	830	775	700
		7.3	26.3	11.6	76.5	99A6	36	2816	2200	1826	1705	1540
10.0/80-12 (3 rib)	9.00X12	264	710	309	2090	10	3.9	2640	2060	1710	1600	1440
		10.4	28	12.2	82.2	124A6	57	5808	4532	3762	3520	3168
10.0/75-15.3 (3 rib)	9	264	760	336.4	2267	10	3.9	3070	2400	1980	1850	1650
						129A6	57	6768	5291	4365	4079	3638
		10.4	29.9	13.2	89.3	14	5.5	3760	2945	2430	2240	2000
						136A6	80	8289	6493	5357	4938	4409
11.5/80-15.3 (3 rib)	9x15.3	290	845	376	2470	10	3.4	3800	2970	2460	2300	2070
						137A6	49	8380	6550	5420	5070	4560
		11.4	33.3	14.9	97.2	14	6.5	4810	3765	3110	2900	2575
						145A6	94	10604	8300	6856	6393	5677
12.5/80-15.3 (3 rib)	9	307	875	371.15	2565	14	4.3	5245	4105	3390	3150	2800
		12.1	34.4	14.6	101.0	148A6	62	11563	9050	7474	6944	6173
400/60-15.5 (3 rib)	13DC	404	874	376.7	2569	16	5.5	5940	4650	3840	3550	3150
						152A6	79	13095	10251	8466	7826	6944
		15.9	34.4	14.8	101.1	148A8	73	14520	11352	9416	8800	7920
						20	5	6600	5160	4280	4000	3600
6.00-16 (3 rib)	4.00EX16	169	712	330	2160	6	2.8	1280	1000	830	775	700
10.5/65-16 (3 rib)	W9 X 16	274	755	346	2335	14	5.6	3500	2730	2270	2120	1910
10.5/65-16	9	274	755	334	2266	10	3.8	2888	2260	1873	1750	1575
		10.8	29.7	13.2	89.2	127A6	55	6370	4980	4130	3860	3470
13.0/55-16 (3 rib)	11X16	336	770	345	2350	14	4.2	3800	2970	2460	2300	2070
		13.2	30.3	13.6	92.5	137A6	61	8360	6534	5412	5060	4554
15.0/55-17 (5 rib)	13.00X17	391	850	14.6	98.0	138A6	38	8558	6688	5566	5192	4680
				384.5	2591	14	3.7	4250	3320	2760	2575	2320
		15.1	102.0	141A6	54	9350	7304	6072	5665	5104		
19.0/45-17 (7 rib)	16	472	866	383.8	2578	14	2.8	5200	4060	3370	3150	2835
		18.6	34.1	15.1	101.4	148A6	41	11460	8950	7430	6950	6250
500/50-17 (5 rib)	16	500	932	424.3	2760	14	2.8	6020	-	3910	3650	3290
		19.7	36.7	16.7	108.6	153A6	41	13244	-	8602	8030	7238
10.5/80-18 (3 rib)	W9X18	274	885	390	2620	10	3.7	3600	2810	2330	2180	1960
		10.8	34.8	15.4	103.1	135A6	54	7920	6182	5126	4796	4312
12.5/80-18 (3 rib)	W9X18	308	965	424.7	2871	12	3.7	4790	3740	3100	2900	2610
						145A6	54	10538	8228	6820	6380	5742
		12.1	38	16.7	113.0	16	4.9	5860	4580	3800	3550	3200
						152A6	71	12892	10076	8360	7810	7040
		148A8	18	5.5	6190	4840	4010	3750	3380			
										154A6	80	13650
150A8	16	4.9	5200	4060	3370	3150	2840					
13.0/65-18	11x18	336	890	400	2745	148A6	71	11460	8950	7430	6950	6260
15.0/70-18	W13X18	391	990	420.9	2992	16	4.25	5693	4451	3692	3450	3105
	13.00X18	15.4	39	16.6	117.8	151A6	62	12551	9813	8139	7606	6845
16.0/70-20 (5 rib)	13.00x20	418	1075	458.5	3158	12	3	6390	5000	4150	3875	3490
		16.5	42.3	18.1	124.3	155A6	44	14058	11000	9130	8525	7678