



Tractor Rear, R1
FARMAX
TUBETYPE

- Robust Lug design for enhanced performance on field and road.
- Dual angle tread design & reinforced carcass for excellent life.
- Suitable for farming and haulage purpose.

Size	Rim	Outer Diameter	Section Width	Static Loaded radius	Rolling Circumference	PR	Inflation Pressure	Loading Index	Speed symbol	Load Capacity
	inches	mm in	mm in	mm in	mm in		bar psi			(kg) lbs
14.9-24	W13x24	1275 50.2	402 15.8	587 23.1	3698 145.6	8	1.8 26	128 / A6	124 / A8	1800 3960
18.4-26	W16LX26	1480 58.3	402 19.4	691 26.8	4292 169.0	12	2.3 33	146/A6	142 / A8	3000 6600
18.4-30	W16LX30	1564 61.6	465 18.3	719 28.3	4536 178.6	12	2.3 33	148 / A6	145 / A8	3250 7150
13.6-38	W12X38	1585 62.4	350 13.8	729 28.7	4506.5 181.0	8	2.0 29	131 / A6	127 / A8	1950 4290
15.6-38	W14X38	1577 62.1	400 15.7	725 28.6	4573 180.1	8	1.8 26	133 / A6	129 / A8	2080 4532
16.9-24	W15Lx24	1330 52.4	426 16.8	612 24.1	3857 151.9	8	1.7 25	133 / A6	129 / A8	2040 4488
11.2-28	W10x28	1205 47.4	295 11.6	554 21.8	3495 137.6	8	2.5 36	118/A6	114 / A8	1320 2904
16.9-38	W15LX38	1685 66.3	426 16.9	775 30.5	4889 192.4	8	3.7 53	141 / A6	137 / A8	2592 5665
12.4-24	W11x24	1159 45.6	307 12.1	533 21.0	3361 132.3	8	2.3 33	121 / A6	117 / A8	1415 3113
14.9-26	W13x26	1375 54.1	386 15.2	633 24.9	3868 157.0	8	1.8 26	130 / A6	126 / A8	2040 4488
16.9-28	W15LX28	1435 56.5	429 16.9	660 26.0	4162 163.8	12	2.4 35	143 / A6	139 / A8	2725 5995
16.9-30	W15LX30	1495 58.9	440 17.3	688 27.1	4336 170.7	10	2.0 29	140 / A6	136 / A8	2455 5401
18.4-34	W16LX34	1650 65.0	465 18.3	759 29.9	4785 188.4	12	2.3 33	150 / A6	146 / A8	3450 7590
13.6-36	W12X36	1535 60.4	350 13.8	706 27.8	4452 175.3	8	2.0 29	129 / A6	125 / A8	1855 4081
18.4-38	W16LX38	1750 68.9	465 18.3	805 31.7	5075 196.8	12	2.3 33	143 / A6	139 / A8	35 7865

All tyres conform to STRO & ETRTO Standards

TYRES

FARM

GENERAL INFORMATION

OFF THE ROAD & INDUSTRIAL TYRES :

CEAT off road tyres are designed for mining, road construction, timber hauling, material handling, port applications and other industrial & construction jobs. Before using them for any other application the manufacturer should be consulted. Wrong selection of tyre, improper handling, poor maintenance and improper driving habits can reduce tyre life.

LOAD & INFLATION PRESSURE : To obtain best results from the tyres correct inflation pressures has to be maintained at all times. It is recommended to check the inflation pressure after long breaks or on weekly basis. If due to heat build up the inflation pressure exceeds additional 1.0 bar (15psi) the load or driving speed has to be lowered.

Load and inflation pressures for the OTR tyres should be determined according to the length of the haul (given in the tables)

MOUNTING & DISMOUNTING :

Always practice correct mounting and dismounting procedures taking all safety measures.

DIMENSIONS : All the dimensions and the tolerances in this catalogue are based on nominal T&RA and ETRTO standard

