


Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in			kmph mph
18.4-34	TL	8	W16	1650	467	4879	748.7	2304.2	1.4	40
		137A8		65	18.4	192	29.4	5080	20	25
13.6-38	TL	8	W12	1565	345	4759	740.8	1750.8	1.9	40
		127A8		61.6	13.5	187.3	29.1	3860	28	25
15.5-38	TL	8	W14L	1570	394	4758	732.7	2060	1.8	40
		129A8		61.8	15.5	187.3	28.8	4542	26	25
16.9-38	TL	8	W15L	1689	429	5043	783	2240	1.65	40
		136A8		66.5	16.9	198.5	30.8	4938	24	25
16.9-38		12	W15L	1689	429	5008	780	2240	2.27	40
		142A8		66.5	16.9	197.2	30.7	4940	33	25
18.4-38	TL	8	W16	1750	462	5099	811.5	2431.2	1.4	40
		139A8		69	18.2	200.7	32	5360	20	25
20.8-38	TL	8	W18A	1834	528	5373	824	2800	1.25	40
				72.2	20.8	211.5	32.4	6173	18	25
20.8-38	TL	10	W18A	1834	528	5373	823.2	3150	1.5	40
		148A8		72.2	20.8	211.5	32.4	6950	22	25
20.8-38	TL	14	W18A	1834	528	5389	829.5	3875	2.2	40
		155A8		72.2	20.8	212.1	32.6	8543	32	25

Size	Rim	Unloaded Dimension		Loaded Static radius	RC	Load Index PR Symbols	Inflation Pressure	Recommended Load							
		Speed													
		Mixed application													
		bar	Static					10	15	20	25	30	40		
		psi	kmph					kmph	kmph	kmph	kmph	kmph	kmph		
mm	mm	mm	mm	mm	mm										
in	in	in	in	in	in										
16.9-30	W15					6PR	1.4	3910	2550	2280	2090	1890	1820	1700	
		430	1484	672	4387	126A8	20	8620	5620	5030	4610	4170	4010	3750	
		16.9	58.4	26.5	172.7	8PR	1.65	4600	3000	2680	2460	2220	2140	2000	
						132A8	24	10140	6610	5910	5420	4890	4720	4410	

GALAXY EARTH-PRO 45 R-1



Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar.

Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.



Size	PR	TYPE	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in			kmph mph
9.5-20	6	TT	W8	940	241	2845	442	825	2.1	40
				37	9.5	112	17.4	1819	30	25
8.3-24	8	TT	W7	998.5	211	3030	470	925	3.1	40
	105A8			39.3	8.3	119.2	18.5	2039	45	25
9.5-24	8	TT	W8	1058	240	3175	490	1120	2.8	40
	112A8			41.6	9.4	125	19.3	2469	41	25
11.2-24	8	TT	W10	1105	284	3355	518	1250	2.4	40
	116A8			43.5	11.1	132	20.4	2756	35	25
	8	TT	W11L	1167	322.6	3461	533	1450	2.3	40
	121A8			46	12.7	136.2	21	3200	33	25
12.4-24	12		W11L	1160	315	3468	543	1850	3.5	40
	129A8			45.7	12.4	136.5	21.4	4080	51	25
13.6-24	8	TT	W12	1219	350.3	3630	550	1550	2	40
	123A8			48	13.7	142.9	21.7	3417	29	25
14.9-24	8	TT	W13	1281	383	3745	574	1800	1.8	40
	128A8			50.4	15	147.4	22.6	3968	26	25
16.9-24	8	TT	W15L	1332	437	4000	600	2060	1.7	40
	133A8			52.4	17.2	157.4	23.6	4542	25	25

Size	PR	TYPE	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
11.2-28	8	TT	W10	1225	289	3681	567	1320	2.4	40
	118A8			48.2	11.3	144.9	22.3	2910	35	25
12.4-28	8	TT	W11L	1278	324	3775	585	1550	2.3	40
	123A8			503	12.7	148.6	23	3417	33	25
13.6-28	8	TT	W12	1310	345	3995	616	1650	2	40
				51.6	13.6	157.2	24.3	3638	29	25
14.9-28	8	TT	W12	1380	384	4141	635	1900	1.8	40
	130A8			54.3	15.1	163	25	4190	26	25
16.9-28	8	TT	W15L	1435	430	4300	650	2180	1.7	40
				56.5	16.9	169.2	25.6	4806	25	25
16.9-30	8	TT	W15L	1502	435	4470	676	2300	1.7	40
	137A8			59.1	17.1	175.9	26.6	5071	25	25
	12*			-----UNDER DEVELOPMENT-----						
18.4-30	8	TT	W16L	1550	465	4545	695	2430	1.4	40
				61	18.3	178.9	27.4	5357	20	25
18.4-30	12		W16L	1550	465	4545	695	2430	1.4	40
	149A8			61	18.3	178.9	27.4	5360	20	25
16.9-34	8	TT	W15	1586	433	4720	725	2430	1.7	40
	139A8			62.4	17	185.8	28.5	5357	25	25
18.4-34	8	TT	W16L	1658	473	4910	740	2650	1.4	40
	142A8			65.2	18.6	193.3	29.1	5842	20	25
	14	TT						3650	2.5	40
	153A8							8050	36	25
12.4-36*	8	TT		-----UNDER DEVELOPMENT-----						
15.5-38	8	TT	W14L	1568	399	4770	734	2060	1.8	40
	133A8			61.7	15.7	188	29	4542	26	25
15.5-38	12		W14L	1570	394	4802	736	2575	2.75	40
	141A8			61.8	15.5	189.1	29	5680	40	25
16.9-38	8	TT	W15L	1686	435	5070	770	2575	1.7	40
	141A8			66.3	17.1	199.6	30.3	5677	25	25
18.4-38	8	TT	W16L	1760	463	5190	790	2725	1.4	40
	143A8			69.2	18.2	204.3	31.1	6008	20	25

GALAXY IRRIGATION R-1 R-1

Irrigation R-1 is specially designed to meet the modern day needs of the irrigation applications. Wide 23 degree angled lugs provide excellent traction. Robust carcass construction with strong sidewall provides protection against damages ensuring zero downtime.



Size	PR	TYPE	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
11.2-38	TL	6PR	W10	1459	284	4390	678	1180	1.8	40
		114A8		57.4	11.2	172.8	26.7	2600	26	25

Size	Rim	Unloaded Dimension		Loaded Static radius	RC	Load Index PR Symbols	Inflation Pressure	Recommended Load							
		Speed													
		Mixed application													
		mm	mm					mm	mm	bar	Static	10	25	30	40
		in	in					in	in	psi	kmph	kmph	kmph	kmph	kmph
11.2-24	W10X24	284	1105	503	3259	6	1.8	2440	1480	1130	1060	950			
	W9X24														
	W10HX24	11.2	43.5	19.8	128.3	110A6	26	5380	3260	2490	2340	2090			
14.9-24	W13 X 24 W12	378	1250	562	3668	8	1.8	4140	2700	1926	1800	1638			
	X 24	14.9	49.2	22.1	144.4	128A8	26	9130	5950	4250	3970	3610			