

Size	PR	Type	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
320/85R36	128A8/128B	TL	W11	1458	325	4315	675	1800	1.6	40
				57.4	12.8	169.9	26.6	3968	23	25
340/85R36	132A8/132B	TL	W12	1495	345	4425	689	2000	1.6	40
				58.9	13.6	174.2	27.1	4409	23	25
340/85R38	133A8/133B	TL	W12	1543	345	4567	714	2060	1.6	40
				60.7	13.6	179.8	28.1	4542	23	25
420/85R38	144A8/144B	TL	W15L	1680	415	5004	655	2800	1.6	40
				66.1	16.3	197	25.8	6173	23	25
460/85R38	149A8/149B	TL	W16L	1740	455	5156	783	3250	1.6	40
				68.5	17.9	203	30.8	7165	23	25
520/85R38	155A8/155B	TL	DW16L	1850	525	5486	830	3875	1.6	40
				72.8	20.7	216	32.7	8543	23	25
320/85R38	143A8/143B	TL	W11	1509	325	4532	701	2725	3.6	40
				59.4	12.8	178.4	27.6	6008	52	25
380/80R38	142A8/142B	TL	W12	1578	375	4721	728	2650	2.4	40
				62.1	14.8	185.9	28.7	5842	35	25
480/80R42	151A8/151B	TL	DW16L	1835	479	5461	841	3450	1.6	40
				72.2	18.9	215	33.1	7606	23	25
520/85R42	157A8/157B	TL	DW16L	1951	516	5766	888	4125	1.6	40
				76.8	20.3	227	35	9094	23	25
320/80R42	141A8/141B	TL	W10	1580	319	4676	739	2575	3.2	40
				62.2	12.6	184.1	29.1	5677	46	25
320/90R42	147A8/147B	TL	W10	1643	319	4940	764	3075	3.6	40
				64.7	12.6	194.5	30.1	6779	52	25
480/80R46	158A8/158B	TL	DW16L	1960	479	5791	880	4250	1.6	40
				77.2	18.9	228	34.6	9370	23	25
520/85R46	158A8/158B	TL	DW16L	2052	516	6096	937	4250	1.6	40
				80.8	20.3	240	36.9	9370	23	25
320/90R46	148A8/148B	TL	W10	1744	319	5258	815	3150	3.6	40
				68.7	12.6	207	32.1	6945	52	25
380/90R46	165A8/165B	TL	W12	1863	380	5582	860	4875	4.7	40
				73.3	15	219.8	33.9	10748	68	25

GALAXY EARTH-PRO 700 SERIES **R-1W**



Galaxy Earth-Pro 700 series radial tire has advanced lug design with steep angle in center for smooth ride, long wear and self-cleaning. It has a lower angle at shoulder for traction. This tire provides greatly improved hillside stability. The Galaxy Earth-Pro 700 radial tire has a highly versatile and modern design providing excellent road wear and ride comfort while at the same time providing high traction in the field. The pads between the lugs act as mud breakers. Also, the reinforced lug and bead areas and improved tread compound provide exceptional working life.



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
300/70R20	120A8/120B	TL	W9	956	293	2833	435	1400	2.4	40
				37.6	11.5	111.5	17.1	3086	35	25
320/70R20	123A8/123B	TL	W10	986	325	2908	445	1550	2.4	40
				38.8	12.8	114.5	17.5	3417	35	25
280/70R20	116A8/116B	TL	W10	912	278	2706	415	1250	2.4	40
				35.9	10.9	106.5	16.3	2756	35	25
320/70R24	116A8/116B	TL	W10	1095	320	3228	498	1250	1.6	40
				43.1	12.6	127.1	19.6	2756	23	25
360/70R24	122A8/122B	TL	W11	1148	358	3386	523	1500	1.6	40
				45.2	14.1	133.3	20.6	3307	23	25
380/70R24	125A8/125B	TL	W12	1191	381	3510	538	1650	1.6	40
				46.9	15	138.2	21.2	3638	23	25

Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
420/70R24	130A8/130B	TL	W13	1247	419	3680	561	1900	1.6	40
				49.1	16.5	144.9	22.1	4189	23	25
480/70R24	138A8/138B	TL	W15L	1316	479	3859	588	2360	1.6	40
				51.8	18.9	151.9	23.1	5203	23	25
320/70R28	119A8/119B	TL	W10	1191	320	3515	546	1360	1.6	40
				46.9	12.6	138.4	21.5	2998	23	25
360/70R28	125A8/125B	TL	W11	1240	358	3658	572	1650	1.6	40
				48.8	14.1	144	22.5	3638	23	25
380/70R28	127A8/127B	TL	W12	1293	381	3815	589	1750	1.6	40
				50.9	15	150.2	23.2	3858	23	25
420/70R28	133A8/133B	TL	W13	1349	419	3980	612	2060	1.6	40
				53.1	16.5	156.7	24.1	4542	23	25
480/70R28	140A8/140B	TL	W15L	1415	480	4173	640	2500	1.6	40
				55.7	18.9	164.3	25.2	5512	23	25
520/70R30	145A8/145B	TL	W16L	1537	516	4531	691	3450	1.6	40
				60.5	20.3	178.4	27.2	7606	23	25
420/70R30	134A8/134B	TL	W13	1397	419.1	4124.96	635	2120	1.6	40
				55	16.5	162.4	25	4674	23	25
480/70R30	141A8/141B	TL	W15L	1478	480	4361	668	2575	1.6	40
				58.2	18.9	171.7	26.3	5677	23	25
480/70R34	143A8/143B	TL	W15L	1580	480	4661	719	2725	1.6	40
				62.2	18.9	183.5	28.3	6008	23	25
520/70R34	148A8/148B	TL	W16L	1640	516	4839	743	3150	1.6	40
				64.6	20.3	190.5	29.3	6945	23	25
480/70R38	145A8/145B	TL	W15L	1681	480	4958	770	2900	1.6	40
				66.2	18.9	195.2	30.3	6393	23	25
520/70R38	150A8/150B	TL	W16L	1755	516	5177	798	3348	1.6	40
				69.1	20.3	203.8	31.4	7381	23	25
710/70R38	172A8/172B	TL	DW23B	1958	716	5768	880	6300	2.4	40
				77.1	28.2	227.1	34.6	13889	35	25
580/70R38	155A8/155B	TL	W18L	1835	577		828	3875	1.6	40
				72.2	22.7	0	32.6	8543	23	25
710/70R42	173A8/173B	TL	DW23B	2050	716	6080	938	6500	2.2	40
				80.7	28.2	239.4	36.9	14330	32	25