

RADIAL TRACTOR

GALAXY EARTH-PRO 850 SERIES R-1W



Galaxy Earth-Pro 850 Series radial tire has an advanced lug design with steep angle in center for smooth ride, long wear and self cleaning. It has a lower angle at shoulder for traction. This tire provides greatly improved hillside stability. The Galaxy Earth-Pro 850 radial tire has a highly versatile and modern design providing excellent road wear and ride comfort while at the same time providing high traction in the field. The pads between the lugs act as mud breakers. Also, the reinforced lug and bead areas and improved tread compound provide exceptional working life.



Size	PR	Type	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
280/85R20	112A8/112B	TL	W10	984	288	2913.4	447	1120	1.6	50
				38.7	11.3	114.7	17.6	2469	23	31
320/85R20	119A8/119B	TL	W11	1045	329	3094	466	1360	1.6	40
				41.1	13	121.8	18.3	2998	23	25
250/85R24	109A8/109B	TL	W8	1036	246	3111	476	1030	1.6	40
				40.8	9.7	122.5	18.7	2271	23	25
280/85R24	115A8/115B	TL	W9	1086	270	3277	495	1215	1.6	40
				42.8	10.6	129	19.5	2679	23	25
320/85R24	122A8/122B	TL	W11	1148	336	3404	515	1500	1.6	40
				45.2	13.2	134	20.3	3307	23	25
340/85R24	125A8/125B	TL	W12	1181	356	3505	530	1650	1.6	40
				46.5	14	138	20.9	3638	23	25
380/85R24	131A8/131B	TL	W12	1252	386	3683	557	1950	1.6	40
				49.3	15.2	145	21.9	4299	23	25
420/85R24	137A8/137B	TL	W15L	1315	418	3835	591	2300	1.6	40
				51.8	16.5	151	23.3	5071	23	25
280/85R28	118A8/118B	TL	W9(W10Alt)	1190	280	3514	548	1320	1.6	40
				46.9	11	138.3	21.6	2910	23	25
320/85R28	124A8/124B	TL	W11	1246	325	3734	565	1600	1.6	40
				49.1	12.8	147	22.2	3527	23	25
380/85R28	133A8/133B	TL	W12	1352	380	3988	604	2060	1.6	40
				53.2	15	157	23.8	4542	23	25
420/85R28	139A8/139B	TL	W15L	1420	418	4166	630	2430	1.6	40
				55.9	16.5	164	24.8	5357	23	25
340/85R28	127A8/127B	TL	W12	1295	360	3835	580	1750	1.6	40
				51	14.2	151	22.8	3858	23	25
460/85R30	145A8/145B	TL	W16L	1530	475	4521	684	2900	1.6	40
				60.2	18.7	178	26.9	6393	23	25
380/85R30	135A8/135B	TL	W12	1408	380	4166	630	2180	1.6	40
				55.4	15	164	24.8	4806	23	25
420/85R30	140A8/140B	TL	W15L	1468	431	4343	658	2500	1.6	40
				57.8	17	171	25.9	5512	23	25
420/90R30	147A8/147B	TL	W13	1518	418	4445	684	3075	2.4	40
				59.8	16.5	175	26.9	6779	35	25
420/90R30	142A8/142B	TL	W13	1518	418	4445	684	2650	1.6	40
				59.8	16.5	175	26.9	5842	23	25
320/85R32	126A8/126B	TL	W11	1357	325	4016	625	1701	1.6	50
				53.4	12.8	158.1	24.6	3750	23	31
420/85R34	142A8/142B	TL	W13	1575	420	4724	715	2650	1.6	40
				62	16.5	186	28.1	5842	23	25
460/85R34	147A8/147B	TL	W16L	1637	479	4801	733	3075	1.6	40
				64.4	18.9	189	28.9	6779	23	25
380/85R34	137A8/137B	TL	W12	1510	380	4496	680	2300	1.6	40
				59.4	15	177	26.8	5071	23	25

Size	PR	Type	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
320/85R36	128A8/128B	TL	W11	1458	325	4315	675	1800	1.6	40
				57.4	12.8	169.9	26.6	3968	23	25
340/85R36	132A8/132B	TL	W12	1495	345	4425	689	2000	1.6	40
				58.9	13.6	174.2	27.1	4409	23	25
340/85R38	133A8/133B	TL	W12	1543	345	4567	714	2060	1.6	40
				60.7	13.6	179.8	28.1	4542	23	25
420/85R38	144A8/144B	TL	W15L	1680	415	5004	655	2800	1.6	40
				66.1	16.3	197	25.8	6173	23	25
460/85R38	149A8/149B	TL	W16L	1740	455	5156	783	3250	1.6	40
				68.5	17.9	203	30.8	7165	23	25
520/85R38	155A8/155B	TL	DW16L	1850	525	5486	830	3875	1.6	40
				72.8	20.7	216	32.7	8543	23	25
320/85R38	143A8/143B	TL	W11	1509	325	4532	701	2725	3.6	40
				59.4	12.8	178.4	27.6	6008	52	25
380/80R38	142A8/142B	TL	W12	1578	375	4721	728	2650	2.4	40
				62.1	14.8	185.9	28.7	5842	35	25
480/80R42	151A8/151B	TL	DW16L	1835	479	5461	841	3450	1.6	40
				72.2	18.9	215	33.1	7606	23	25
520/85R42	157A8/157B	TL	DW16L	1951	516	5766	888	4125	1.6	40
				76.8	20.3	227	35	9094	23	25
320/80R42	141A8/141B	TL	W10	1580	319	4676	739	2575	3.2	40
				62.2	12.6	184.1	29.1	5677	46	25
320/90R42	147A8/147B	TL	W10	1643	319	4940	764	3075	3.6	40
				64.7	12.6	194.5	30.1	6779	52	25
480/80R46	158A8/158B	TL	DW16L	1960	479	5791	880	4250	1.6	40
				77.2	18.9	228	34.6	9370	23	25
520/85R46	158A8/158B	TL	DW16L	2052	516	6096	937	4250	1.6	40
				80.8	20.3	240	36.9	9370	23	25
320/90R46	148A8/148B	TL	W10	1744	319	5258	815	3150	3.6	40
				68.7	12.6	207	32.1	6945	52	25
380/90R46	165A8/165B	TL	W12	1863	380	5582	860	4875	4.7	40
				73.3	15	219.8	33.9	10748	68	25

GALAXY EARTH-PRO 700 SERIES **R-1W**



Galaxy Earth-Pro 700 series radial tire has advanced lug design with steep angle in center for smooth ride, long wear and self-cleaning. It has a lower angle at shoulder for traction. This tire provides greatly improved hillside stability. The Galaxy Earth-Pro 700 radial tire has a highly versatile and modern design providing excellent road wear and ride comfort while at the same time providing high traction in the field. The pads between the lugs act as mud breakers. Also, the reinforced lug and bead areas and improved tread compound provide exceptional working life.



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
300/70R20	120A8/120B	TL	W9	956	293	2833	435	1400	2.4	40
				37.6	11.5	111.5	17.1	3086	35	25
320/70R20	123A8/123B	TL	W10	986	325	2908	445	1550	2.4	40
				38.8	12.8	114.5	17.5	3417	35	25
280/70R20	116A8/116B	TL	W10	912	278	2706	415	1250	2.4	40
				35.9	10.9	106.5	16.3	2756	35	25
320/70R24	116A8/116B	TL	W10	1095	320	3228	498	1250	1.6	40
				43.1	12.6	127.1	19.6	2756	23	25
360/70R24	122A8/122B	TL	W11	1148	358	3386	523	1500	1.6	40
				45.2	14.1	133.3	20.6	3307	23	25
380/70R24	125A8/125B	TL	W12	1191	381	3510	538	1650	1.6	40
				46.9	15	138.2	21.2	3638	23	25