



MAXAM

MS301

E3/L3

Standard E3/L3 rock lug pattern combines excellent traction and high resistance to wear and cutting.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear
- Increased net-to-gross for improved tread life

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	
17.5R25	★★	TL	14.00/1.5	52.7	17.7	35	94	18700	76	12000	
				1339	449	28	650	8500	525	5450	182A2/167B
20.5R25	★★	TL	17.00/2.0	59.0	20.4	37	94	25400	76	16100	193A2/177B
				1499	517	30	650	11500	525	7300	
23.5R25	★★	TL	19.50/2.5	63.4	23.9	41	94	32000	76	20400	201A2/185B
				1611	608	33	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.8	26.7	45	94	40800	76	25400	209A2/193B
				1748	679	36	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	74.3	30.0	49	94	49400	76	30900	216A2/200B
				1886	763	39	650	22400	525	14000	

