



MAXAM MS401

E4

Deep grooved tread design provides excellent traction in rigid dump truck applications. Ideal for applications requiring maximum road grip and high site TKPH.

- Excellent traction in all off road conditions
- Deep tread grooves provide cooler running tread for high site TKPH
- Wide, square footprint distributes load for minimal haul road disturbance
- Reinforced bead, shoulder and sidewall for increased cut resistance
- Heat resistant undertread reduces tire temperature
- Multiple tread compound options target specific site requirements

Applications:



Size	Rating	Type	Rim	O.D.		S.W.		T.D.		Tread Compound	TMPH/ TKPH	Infl. P.		L.C.C. (lbs/kg)	L.I.
				in	mm	in	mm	32nds	mm			psi	KPa		
12.00R24	★★★	TT / TL	8.50V	49.3	12.0	40	Standard	---	130	9900	160F				
				1251	305	32	Cut Resistant					900	4500		
14.00R24	★★★	TT	10.00W	55.1	15.6	45	Standard	82/120	109	12800	169B				
				1400	395	36	Cut Resistant	62/91	750	5800					
14.00R25	★★★	TT / TL	10.00/1.5	55.1	15.6	45	Standard	82/120	109	12800	169B				
				1400	395	36	Cut Resistant	62/91	750	5800					
18.00R25	★★	TL	13.00/2.5	65.7	20.3	62	Standard	---	102	20400	185B				
				1669	515	49	Cut Resistant					700	9250		
				73.6	20.3	66	Standard					146/213	102	24000	
18.00R33	★★	TL	13.00/2.5	1876	516	52	Cut Resistant	118/173	700	10900	191B				
							Heat Resistant	171/249							
				78.0	21.8	77	Standard	187/273				102	30900		
21.00R33	★★	TL	15.00/3.0	1982	554	61	Cut Resistant	151/221	700	14000	200B				
							Heat Resistant	218/318							
				80.7	23.2	74	Standard	187/273				102	32000		
21.00R35	★★	TL	15.00/3.0	2050	590	58	Cut Resistant	151/221	700	14500	201B				
							Heat Resistant	218/318							
				85.4	26.2	83	Standard	247/361				102	40800		
24.00R35	★★	TL	17.00/3.5	2170.0	666.0	65	Cut Resistant	200/292	700	18500	209B				
							Heat Resistant	288/421							
							Standard	368/537				102	60000		
27.00R49	★★	TL	19.50/4.0	106.7	28.9	88	Ultra Cut Resistant	257/375	700	27250	223B				
							Cut Resistant	319/465							
				2710	734	71	Heat Resistant	430/627							

