



MAXAM MS901

BACKHOE - INDUSTRIAL SERVICE

An aggressive R4 tread pattern for applications requiring high traction.

- Wide tread design for increased flotation
- Wear and cut resistant compound
- Deep undertread for improved puncture resistance
- Reinforced bead and sidewall for excellent stability

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)		L.I.
				in mm	in. mm	32nds mm	psi KPa	5 mph 10 kph	25 mph 40 kph	
12.5/80-18 (340/80-18)	12	TL	W9	38.7	12.2	33	58	7500	6000	143A8
				983	310	26	400	3405	2725	
14.9-24	12	TL	W13	48.2	13.1	32	42	8000	6400	145A8
				1224	333	25	280	3625	2900	
16.9-24	12	TL	W15L	50.8	16.0	33	38	8940	7150	149A8
				1290	406	26	260	4060	3250	
18.4-26	12	TL	W16L	56.1	18.7	36	36	11000	8800	156A8
				1425	475	28	250	5000	4000	
16.9-28	16	TL	W16L	56.1	18.7	36	45	13125	10500	162A8
				1425	475	28	310	6000	4750	
18.4-28	12	TL	W15L	55.5	17.2	34	38	9815	7850	152A8
				1410	437	27	260	4500	3550	
18.4-28	14	TL	W15L	55.5	17.2	34	44	10690	8550	155A8
				1410	437	27	300	4875	3875	
18.4-28	12	TL	W16	57.1	17.4	36	36	11375	9100	157A8
				1450	442	28	250	5155	4125	

