



MAXAM

MS906

SKID STEER

Deep R4 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full, flat profile with self-cleaning stepped tread improves performance
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces tread chunking

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	
				in mm	in. mm	32nds mm		psi KPa	5 mph 10 kph 30 mph 50 kph
5.70-12	6	TL	4.50	22.4 569	5.7 145	18 14	60 415	1450 660	900 410
23x8.50-12	6	TL	7JA	22.9 583	8.5 214	17 13	50 340	1820 825	1145 515
				22.9 583	8.5 214	17 13	65 450	2150 975	1355 615
	12	TL	7JA	22.9 583	8.5 214	17 13	75 515	2680 1215	1690 760
				26.9 682	8.7 221	18 14	60 415	2910 1320	1820 825
27x8.50-15	8	TL	7JA	27.6 701	10.4 254	24 19	100 690	7800 3500	5040 2250
7.00-15	6	TL	5.50	29.9 760	7.8 198	21 16	60 415	3180 1400	2015 920
				29.9 760	7.8 198	21 16	70 480	3640 1650	2290 1030
	8	TL	5.50	31.0 787.0	15.1 384	30 23	45 310	4400 2000	2760 1250
10-16.5	10	TL	8.25	30.2 768	10.7 271	21 16	75 515	4710 2130	2950 1330
12-16.5	12	TL	9.75	32.8 834	13.0 331	25 20	80 550	6320 2850	4030 1830
14-17.5	14	TL	10.50	36.2 920	14.2 360	33 26	80 550	8540 3870	5360 2430
15-19.5	14	TL	11.75	40.2 1020	15.3 389	33 26	70 480	10060 4560	6425 2915
				40.2 1020	15.3 389	33 26	80 550.0	10880 4935	6930 3150
	16	TL	11.75	40.2 1020	15.3 389	33 26	80 550.0	10880 4935	6930 3150

