



MAXAM

MS302

E3/L3

Heavy duty E3/L3+ lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to minimize vibration at haul speeds and provides the lowest cost-per-hour.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear
- Increased net-to-gross and tread depth for highest tread life
- Offset, reinforced lugs minimize vibration at haul speeds

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	
20.5R25	★★	TL	17.00/2.0	58.8	20.5	42	94	25400	76	16100	193A2/177B
				1493	521	33	650	11500	525	7300	
23.5R25	★★	TL	19.50/2.5	63.5	23.6	47	94	32000	76	20400	201A2/185B
				1613	599	37	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.6	26.5	50	94	40800	76	25400	209A2/193B
				1742	672	40	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	74.5	30.0	53	94	49400	76	30900	216A2/200B
				1893	763	42	650	22400	525	14000	
550/65R25	★	TL	17.00/2.0	53.1	21.5	44	69	18700	62	13900	182A2/172B
				1347	547	35	475	8500	425	6300	
650/65R25	★★	TL	19.50/2.5	58.2	25.0	46	91	30900	62	17600	200A2/180B
				1479	636	37	625	14000	425	8000	
750/65R25	★★	TL	24.00/3.0	63.3	29.4	52	91	40800	62	23400	209A2/190B
				1608	747	41	625	18500	425	10600	
775/65R29	★★	TL	25.00/3.5	68.5	30.5	57	91	45400	62	26800	213A2/195B
				1740	775	45	625	20600	425	12150	
875/65R29	★★	TL	27.00/3.5	73.4	33.5	60	91	56800	62	34200	221A2/203B
				1865	851	48	625	25750	425	15500	

