



# MAXAM

# MSV01

## HIGHWAY SERVICE

For cranes operating in highway and off-the-road applications.

- F-speed rated (50mph/80kph)
- Low road noise and reduced vibration for improved operator comfort
- Excellent stability and handling response at highway speeds
- Deep tread grooves and traction lug pattern improve wet grip and off-road performance

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	50 mph 80 kph	
14.00R24 (385/95R24)	★★★	TT	10.00 W	54.2	15.7	29	130	13200	170F
				1376	399	23	900	6000	
14.00R25 (385/95R25)	★★★	TL	9.50/1.7 CR 10.00/1.5	54.2	15.7	29	130	13200	170F
				1376	399	23	900	6000	
16.00R25 (445/95R25)	★★★	TL	11.00/1.7 CR 11.25/2.0	59.1	18.3	34	130	14800	174F
				1500	465	27	900	6700	
20.5R25 (525/80R25)	★★★	TL	17.00/1.7 CR 17.00/2.0	59.2	20.3	37	102	16100	177F
				1504	516	30	700	7300	

