



KNK33

FRONT TRACTOR TYRES

- Extra strong with its increased tread depth
- Comfortable driving in the field and on the road by pattern design
- Mud-free pattern

KNK33

Product Code	Tyre Size & Ply Rating	TT/ TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Load & Pressure		Dynamic Rolling Circumference	Static Loaded Radius
			Section Width	Overall Diameter			Tyre Load Capacity	Tyre Pressure At Max. Load		
			mm	mm			kg	Psi		mm
U3162111OZK	6.00-16 6PR	TT	165	735	88	A6	560	48	2206	335
U3162121OZK	6.00-16 8PR	TT	165	735	93	A6	650	48	2206	335
U3163111OZK	6.50-16 6PR	TT	175	760	91	A6	615	45	2277	345
U3163121OZK	6.50-16 8PR	TT	175	760	97	A6	730	54	2277	345
U3164211OZK	7.50-16 6PR	TT	205	805	98	A6	750	41	2404	363
U3164221OZK	7.50-16 8PR	TT	205	805	103	A6	875	54	2404	363
U3191011OZK	6.00-19 6PR	TT	165	814	93	A6	650	48	2453	374



KNK35

FRONT TRACTOR TYRES

- Suitable to asphalt and land usage
- Excellent maneuverability and nondirectional use
- Resistant structure against punctures
- Straight movement stability in soft land

KNK35

Product Code	Tyre Size & Ply Rating	TT/ TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Load & Pressure		Dynamic Rolling Circumference	Static Loaded Radius
			Section Width	Overall Diameter			Tyre Load Capacity	Tyre Pressure At Max. Load		
			mm	mm			kg	Psi		mm
U3161011OZK	5.50-16 6PR	TT	150	710	86	A6	530	54	2135	325
U3162211OZK	6.00-16 6PR	TT	165	735	88	A6	560	48	2206	335
U3162221OZK	6.00-16 8PR	TT	165	735	93	A6	650	48	2206	335
U3163211OZK	6.50-16 6PR	TT	175	760	91	A6	615	45	2277	345
U3163221OZK	6.50-16 8PR	TT	175	760	97	A6	730	54	2277	345
U3164311OZK	7.50-16 6PR	TT	205	805	98	A6	750	41	2404	363
U3164321OZK	7.50-16 8PR	TT	205	805	103	A6	875	54	2404	363
U3166021OZK	9.00-16 8PR	TT	234	855	111	A6	1090	45	2545	383
U3167021OZK	10.00-16 8PR	TT	274	895	115	A6	1215	41	2658	399
U3168021OZK	11.00-16 8PR	TT	315	965	118	A6	1320	36	2856	427
U3181221OZK	7.50-18 8PR	TT	205	860	106	A6	950	54	2575	390