

TYRE SIZE	TREAD PATTERN	PLY RATING	RIM WIDTH (inch)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	LOAD CAPACITY (kg)	INFLATION PRESSURE (bar)
-----------	---------------	------------	------------------	--------------------	-----------------------	--------------------	--------------------------

DRIVE WHEEL TYRES (R-1 & R-3) FOR TRACTORS

20"	8.00-20	GRIPKING	6	6.0	220	965	920	2.1
	8.3-20	GRIPKING	6	6.0	211	955	710	2.4
	9.5-20	GRIPKING	8	7.0	241	945	975	2.8
	11.2-20	GRIPKING	8	10.0	284	1005	1150	2.6
22"	8.3-22	GRIPKING	6	7.0	211	950	775	2.1
	9.5-22	GRIPKING	6	8.0	241	1000	1100	2.4
24"	8.3-24	GRIPKING	6	6.0	211	995	810	2.4
	9.5-24	GRIPKING	8	7.0	241	1050	1110	2.4
	11.2-24	GRIPKING	8	10.0	284	1105	1250	2.4
	12.4-24	GRIPKING	8	11.0	315	1170	1415	2.3
		GRIPKING	12	11.0	315	1170	1800	3.4
	13.6-24	GRIPKING	8	12.0	345	1210	1545	2.0
	14.9-24	GRIPKING	8	13.0	378	1265	2375	3.0
	15.5/80-24	GRIPKING	12	13.0	394	1262	4125	3.1
		GRIPKING	16	13.0	394	1262	4875	4.9
	13.6-26	GRIPKING	8	12.0	345	1260	1650	1.8
	14.9-26	GRIPKING	8	13.0	378	1315	1820	1.8
	16.9-26	GRIPKING	10	14.0	429	1385	2455	2.0
26"	18.4-26	PK-319	12	16.0	470	1465	3000	2.4
	23.1-26	SW-206	8	20.0	588	1560	2900	1.1
		SW-206	12	20.0	588	1560	3650	1.7
		SW-206	16	20.0	588	1560	4375	2.3
	11.2-28	GRIPKING	8	10.0	284	1205	1320	2.4
	12.4-28	GRIPKING / GK-111	8	11.0	315	1265	1550	2.3
		FIELDKING / POWERLUG / FS-888	12	11.0	315	1270	1990	3.1
28"		KRISHIKING	12	11.0	315	1275	1990	3.1
	13.6-28	GRIPKING	8	12.0	345	1320	1650	2.4
		FIELDKING / POWERLUG / KRISHIKING	12	12.0	345	1330	2075	2.4
	14.9-28	GRIPKING	8	13.0	378	1365	1900	1.8
		GRIPKING / FIELDKING	12	13.0	378	1365	2120	2.4
	16.9-28	GRIPKING	8	15.0	429	1435	2180	1.7
		GRIPKING / FIELDKING	12	15.0	429	1435	2730	2.4
	16.9-30	GRIPKING	8	15.0	429	1485	2300	1.7
		GRIPKING	12	15.0	429	1485	2730	2.5
	18.4-30	GRIPKING	10	16.0	470	1560	2650	1.6
30"		GRIPKING	14	16.0	470	1560	3450	2.5
	16.9-34	GRIPKING	8	15.0	430	1590	2430	1.7
		GRIPKING	14	15.0	430	1590	3025	2.6
	18.4-34	GRIPKING	8	16.0	470	1660	2650	1.4
34"		GRIPKING	14	16.0	470	1660	3550	2.6
	20.8-34	GRIPKING	14	18.0	528	1760	3200	1.4
		GRIPKING	18	18.0	528	1760	3650	1.8
	13.6-38	GRIPKING	8	12.0	345	1565	1950	2.0
	14.00-38	GRIPKING	12	13.0	355	1570	2430	2.9
	14.9-38	GRIPKING PLUS	12	14.0	378	1685	2575	3.0
	15.5-38	GRIPKING PLUS	8	14.0	400	1595	2060	1.8
		GRIPKING PLUS	12	14.0	400	1595	2550	3.0
	16.9-38	GRIPKING	8	15.0	429	1585	2575	1.8
		GRIPKING	14	15.0	429	1585	3400	2.3
38"	18.4-38	GRIPKING	8	16.0	470	1770	2725	1.4
		GRIPKING	14	16.0	470	1770	3650	2.3
	20.8-38	GRIPKING	14	18.0	528	1840	4000	1.9
		GRIPKING	28	18.0	528	1840	5850	4.4
	18.4-42	GRIPKING	14	16.0	467	1850	3875	2.6