






# Flotation Trailer Tyre



**FL 09**

Tyre Size 	Pattern	Rim Width (inch) 		Unloaded Inflated Dimensions ± 2%		Static Loaded Radius (mm)	Rolling Circumference (mm) ± 2.5% 	PR	Free / Drive Wheel	Type	Inf. Pr	Recommended Load, kg (lbs)										
				Speed, km/h (mph)																		
		REC	ALT	SW (mm) 	OD (mm) 	mm	mm		mm			mm	Load Index	bar	Free Rolling				Drive Wheel			
		in	in	in	in										in	in	in	in	10	25	40	50
												6	16	25	31	6	16	25	31			
385/65-22.5	FL09	AG 11.75	AG 13.00	423	4052	463	3017	16	154A8	TL	4.0	5250	4465	3750	3375	3605	3065	2575	2320			
				16.7	159.5	18.2	118.8		141A8		58	11575	9845	8270	7440	7950	6760	5680	5115			
400/55-22.5	FL09	AG 11.75	AG 13.00	423	1042	452	2993	12	146A8	TL	3.0	4200	3570	3000	2700	2970	2525	2120	1910			
									134A8		44	9260	7870	6615	5955	6550	5570	4675	4210			
				16.7	41.0	17.8	117.8	16	152A8	TL	4.0	4970	4225	3550	3195	3500	2975	2500	2250			
									140A8		58	10960	9315	7830	7045	7720	6560	5515	4960			
400/60-22.5	FL09	AG 11.75	AG 13.00	410	1045	463	3017	18	156A8	TL	4.5	5600	4760	4000	3600	3815	3245	2725	2455			
				16.1	41.1	18.2	118.8		144A8		65	12350	10495	8820	7940	8410	7155	6010	5415			
500/45-22.5	FL09	AG 16.00	-	503	1015	455	3022	12	149A8	TL	2.4	4550	3870	3250	2925	3135	2665	2240	2015			
									136A8		35	10035	8535	7165	6450	6915	5875	4940	4445			
				19.8	40.0	17.9	119.0	16	155A8	TL	3.2	5425	4610	3875	3490	3710	3155	2650	2385			
									142A8		46	11960	10165	8545	7695	8180	6955	5845	5260			
500/60-22.5	FL09	AG 16.00	-	505	1200	523	3467	12	157A8	TL	2.4	5775	4910	4125	3715	4060	3450	2900	2610			
									145A8		35	12735	10825	9095	8190	8950	7605	6395	5755			
				19.9	47.2	20.6	136.5	16	163A8	TL	3.2	6825	5800	4875	4390	4830	4105	3450	3105			
									151A8		46	15050	12790	10750	9680	10650	9050	7605	6845			
550/45-22.5	FL09	AG 16.00	-	550	1055	479	3121	12	153A8	TL	2.1	5110	4345	3650	3285	3605	3065	2575	2320			
									141A8		30	11270	9580	8050	7245	7950	6760	5680	5115			
				21.7	41.5	18.9	122.9	16	159A8	TL	2.8	6125	5205	4375	3940	4305	3660	3075	2770			
									147A8		41	13505	11475	9645	8690	9495	8070	6780	6110			
550/60-22.5	FL09	AG 16.00	-	550	1250	542	3569	12	160A8	TL	2.1	6300	5355	4500	4050	4410	3750	3150	2835			
									148A8		30	13890	11810	9925	8930	9725	8270	6945	6250			
				21.7	49.2	21.3	140.5	16	167A8	TL	2.8	7630	6485	5450	4905	5250	4465	3750	3375			
									154A8		41	16825	14300	12015	10815	11575	9845	8270	7440			
600/50-22.5	FL09	AG 20.00	-	618	1170	511	3389	16	165A8	TL	2.6	7210	6130	5150	4635	5110	4345	3650	3285			
				24.3	46.1	20.1	133.4		153A8		38	15900	13515	11355	10220	11270	9580	8050	7245			
700/40-22.5	FL09	AG 24.00	-	702	1158	499	3308	16	166A8	TL	2.25	7420	6305	5300	4770	5250	4465	3750	3375			
				27.6	45.6	19.6	130.2		154A8		33	16360	13905	11685	10520	11575	9845	8270	7440			

TL- Tubeless

E-marking available for all the sizes in this segment