


Implement Mixed Application Tyres >>

**TS 09S****IM 45****IM 54****IM 63****IM 72****IM 99****IM 108****MT 63 / MT 63T****MT 45**

Implement Mixed Application Tyres

Tyre Size 	Pattern	Rim Width (inch) 	Unloaded Inflated Dimensions ± 2%		Static Loaded Radius (mm)	Rolling Circumference (mm) ±2.5% 	PR	Type	Load Capacity (kg)										Inflation Pressure	
			SW (mm) 	OD (mm) 					10 (km/h)		20 (km/h)		25 (km/h)		30 (km/h)		40 (km/h)			
			REC	mm					mm	mm	mm	Free Wheel	Drive Wheel	Free Wheel	Drive Wheel	Free Wheel	Drive Wheel	Free Wheel		Drive Wheel
3.50-8	IM63	2.50A	92	395	184	1167	2	TT	170	120	150	105	140	100	132	92.5	120	85	1.50	
4.00-8	IM45	3.00D	106	415	193	1235	2		200	140	175	125	165	115	155	109	140	100	1.50	
4.00-10	IM45	3.00D	106	468	217	1391	2		240	165	210	145	200	135	185	128	165	115	1.50	
							4		340	240	300	210	285	200	265	185	240	165	2.75	
5.0-10	IM54	4.00	130	510	233	1514	2		330	230	295	205	275	195	257	180	230	160	1.00	
							4		350	245	310	215	290	205	272	190	245	170	2.25	
4.00-12	IM45	3.00D	120	525	244	1551	2		275	195	240	170	225	160	212	150	190	135	1.50	
5.00-12	IM45	3.50D	139	580	260	1705	2		330	230	295	205	275	195	257	180	230	160	1.25	
							4		485	340	425	300	400	285	375	265	340	240	2.25	
6.5/80-12	IM54	5.00	163	587	274	1783	4		645	460	570	405	535	380	500	355	450	320	2.40	
7.00-12	IM45	4.25	196	690	321	2038	6	TT/TL	840	580	740	515	695	480	650	450	585	405	3.60	
11.0/65-12	IM45	9.00	260	700	330	2097	6	TT	890	630	785	555	740	520	690	487	620	440	2.50	
							8	TT/TL	1290	890	1140	785	1070	740	1000	690	900	620	2.20	
5.00-15	IM45	3.50D	133	655	300	1937	4	TT	1520	1065	1345	940	1265	885	1180	825	1060	745	2.90	
							6		565	395	500	350	470	330	437	307	395	275	2.25	
6.5/80-15	IM99	2.40	165	655	313	2010	4		720	500	640	440	600	415	560	387	505	350	3.50	
							6		775	550	685	485	640	455	600	425	540	385	2.40	
8.0/75-15	IM45	7.00	210	700	332	2112	6	TT/TL	970	705	855	620	805	585	750	545	675	490	3.60	
10.0/75-15.3	MT63T	9.00	275	795	367	2339	8	TL	1030	720	910	640	855	600	800	560	720	505	2.50	
							10		1755	1225	1550	1085	1455	1015	1360	950	1225	855	3.10	
							14		2000	1405	1765	1245	1660	1165	1550	1090	1395	980	3.90	
	TS09s	9.00	272	785	367	2339	8		2450	1705	2165	1505	2035	1410	1900	1320	1710	1190	5.50	
							10		1755	1225	1550	1085	1455	1015	1360	950	1225	855	3.10	
							14		2000	1405	1765	1245	1660	1165	1550	1090	1395	980	3.90	
11.5/80-15.3	MT63T	9.00	312	875	396	2599	10		2515	1755	2225	1550	2085	1455	1950	1360	1755	1225	3.40	
							14		3135	2195	2770	1940	2600	1820	2430	1700	2185	1530	4.75	
	IM45		9.00	292	875	411	2559		8	2195	1520	1940	1345	1820	1265	1700	1180	1530	1060	2.70
									10	2515	1755	2225	1550	2085	1455	1950	1360	1755	1225	3.40
27x10-15.3	IM45	8.00	255	685	321	2038	8	TT/TL	3135	2195	2770	1940	2600	1820	2430	1700	2185	1530	4.75	
400/60-15.5	IM72	AG 13.00	405	865	387	2608	14	TL	1290	905	1140	800	1070	750	1000	700	900	630	3.00	
							18		3515	2450	3105	2165	2915	2035	2725	1900	2455	1710	3.50	
							22		4195	2840	3705	2510	3480	2355	3250	2200	2925	1980	4.50	
6.00-16	IM45	4.00E	170	735	350	2189	6	TT	4710	3195	4160	2820	3905	2650	3650	2475	3285	2230	5.50	
6.50-16	IM108	4.50E	175	742	351	2230	6	TT/TL	890	630	785	555	740	520	690	487	620	440	2.75	
7.50-16	IM54	5.50F	200	775	378	2381	8	TT	1000	705	885	620	830	585	775	545	700	490	2.75	
8.25-16	IM54	6.00F	232	825	386	2451	8	TL	1195	840	1055	740	990	695	925	650	835	585	3.75	
							6		1445	1000	1275	885	1200	830	1120	775	1010	700	3.25	
8	1365	970	1210	855	1135	805	1060		750	955	675	2.30								
15.0/55-17	IM45	13.00	385	885	419	2658	10		1615	1130	1425	995	1340	935	1250	875	1125	790	3.10	
							14		2735	1935	2415	1710	2270	1605	2120	1500	1910	1350	2.60	
							18		3320	2320	2935	2050	2755	1925	2575	1800	2320	1620	3.70	
							14	3870	2735	3420	2415	3210	2270	3000	2120	2700	1910	4.90		
500/50-17	IM72	16.00	480	925	418	2765	14	TT/TL	4195	2890	3705	2555	3480	2395	3250	2240	2925	2015	2.80	
							16		4580	3135	4045	2770	3800	2600	3550	2430	3195	2185	3.20	
							18		4840	3320	4275	2935	4015	2755	3750	2575	3375	2320	3.60	
7.50-18	IM45	5.50	210	860	400	2540	8	TL	1615	1160	1425	1025	1340	965	1250	900	1125	810	3.70	
10.5/80-18	MT45	9.00	282	911	406	2666	10		2515	1755	2225	1550	2085	1455	1950	1360	1755	1225	3.70	
							14		3045	2130	2690	1880	2525	1765	2360	1650	2125	1485	5.20	
12.0/75-18	MT63	W9	295	920	451	2779	10		2515	1755	2225	1550	2085	1455	1950	1360	1755	1225	3.70	
							12		3135	2195	2770	1940	2600	1820	2430	1700	2185	1530	4.00	
12.5/80-18	MT45	9.00	315	990	439	2901	12		3420	2385	3020	2110	2835	1980	2650	1850	2385	1665	3.70	
							14		3870	2735	3420	2415	3210	2270	3000	2120	2700	1910	4.30	
	IM45		9.00	310	987	438	2892		12	3420	2385	3020	2110	2835	1980	2650	1850	2385	1665	3.70
									16	4065	2810	3590	2485	3370	2335	3150	2180	2835	1960	4.90
4.50-19	IM45	3.00	124	727	342	2171	4	TT	580	405	515	360	480	335	450	315	405	285	3.10	
7.50-20	IM45	5.50	215	910	427	2707	8		1615	1130	1425	995	1340	935	1250	875	1125	790	3.40	
9.50-20	IM45	8.00	245	955	444	2821	6		1065	740	940	655	885	615	825	575	745	520	2.10	
405/70-20	MT72	13.00	407	1080	475	3280	14	TL	-	5220	-	4350	-	3915	-	3625	-	3250*	3.50	
15.5/80-24	IM54	12.00	425	1255	565	3649	12	TL	5320	3740	4705	3305	4415	3105	4125	2900	3715	2610	3.00	
							14		5805	4065	5130	3590	4815	3370	4500	3150	4050	2835	3.50	
							16		6290	4320	5555	3820	5215	3585	4875	3350	4390	3015	4.00	