

LIFT EX

GRI
WE'LL GET YOU THERE

Excellent
run time

Superior
self-cleaning properties

Sturdy
and flexible sidewall

Exceptional
heat dissipation



LIFT EX PNEUMATIC FORKLIFT TIRE

A Pneumatic Material Handling Tire engineered for heavy duty use on forklift trucks and other industrial vehicles. These tires have a large footprint and a tread that assures optimal traction under every condition. The sidewalls are enhanced by multiple layers of reinforcement and a wide rim guard. The augmented contact area and the reinforced sidewall ensures high load carrying capacity.

LIFT EX is best suited for...

- High abrasion resistance
- Maximum stability, safety and comfort
- Cool running temperature
- Extremely low rolling resistance



TECHNICAL DATA

TYRE SIZE	PR	TT / TL	TUBE	VALVE	FLAP	RIM		Unloaded Inflated Dimension		Speed Index	LOAD CAPACITY								Inflation Pressure			
						Rec. inch	Alt. inch	± 2 % mm	± 2 % mm		FORK LIFT TRUCK				OTHER VEHICLE						STATIC LOADER	
											UP TO 16 MPH / 25 KMPH		5 MPH (A2)		15 MPH (A5)		0 MPH					
						MAX. LOAD		MAX. LOAD			MAX. LOAD		MAX. LOAD		MAX. LOAD		LOAD WHEEL				STEERING WHEEL	
Load Index	kgs	Load Index	kgs	Load Index	kgs	Load Index	kgs	Load Index	kgs	Load Index	kgs	Load Index	kgs	PSI	Bar							
8.0																						
5.00-8	8	TT	5.00-8	JS2	5.00-8	3.0D	3.25 I	135	467	A 5	115	1215	106	950	115	1215	106	950	120	1400	120	8.3
18x7-8	16	TT	18X7-8	V3-02-05	18X7-8	4.33 R	5.00F	173	472	A 5	134	2145	125	1650	134	2145	125	1650	140	2500	145	10
9.0																						
6.00-9	10	TT	6.00-9	JS2	6.00-9	4.00E		168	536	A 5	127	1750	118	1320	127	1750	118	1320	132	2000	123	8.5
10.0																						
6.50-10	10	TT	6.50-10	JS2	6.50-10	5.00F	5.50F	183	592	A 5	131	1950	122	1500	131	1950	122	1500	136	2240	112	7.8
23X9-10	20	TT	23X9-10	TR177A	23X9-10	6.5F		236	579	A5	151	3450	142	2650	151	3450	142	2650	156	4000	145	10
12.0																						
7.00-12	12	TT	7.00-12	TR75A	7.00-12	5.00S		196	681	A5	142	2650	133	2060	142	2650	133	2060	147	3075	123	8.5
7.00-12	14	TT	7.00-12	TR75A	7.00-12	5.00S		196	681	A 5	143	2725	134	2120	143	2725	134	2120	148	3150	130	9
15.0																						
8.15-15	14	TT	8.15-15	TR75A	8.15-15	7	7.0BD	218	706	A 5	154	3750	145	2900	154	3750	145	2900	159	4375	130	9
8.25-15	14	TT	7.50/8.25-15	TR177A	7.00/8.25-15	6.5	7	246	841	A 5	158	4250	149	3250	158	4250	149	3250	163	4875	116	8
250-15	16	TT	250-15	TR 77 A	250/300/10L-15	7.5		231	734	A 5	159	4375	150	3350	159	4375	150	3350	164	5000	120	8.3
250-15	20	TT	250-15	TR 77 A	250/300/10L-15	7.5		231	734	A 5	165	5150	156	4000	165	5150	156	4000	170	6000	152	11
300-15	18	TT	300-15	TR 77 A	250/300/10L-15	8		277	851	A 5	170	6000	161	4625	170	6000	161	4625	175	6900	109	7.5
300-15	20	TT	300-15	TR 77 A	250/300/10L-15	8		277	815	A 5	172	6300	163	4875	172	6300	163	4875	177	7300	138	9.5

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. If any tire covered by this warranty is identified as unserviceable tire due to a material / workmanship /any other manufacturing defect, we will either repair the tire or make an allowance on purchase of new tire as per the current price of a new tire by the percentage of original tread worn off at the time of making the claim.

The cost of transportation, service, and sales tax already paid will be borne by the owner of the claimed tire. This limited warranty is made for the exclusive benefit of the tire owner actually using the product. No other warranty of liability, expressed or implied, is applicable to this limited warranty or to our products.

Business today is complex, ambiguous and uncertain – a little like life itself. To help you advance and attain your goals, you need something that is completely the opposite. GRI tires are robustly engineered and relentlessly tested to give you assured performance, so you can get a grip on things that really matter to you. Whatever your ambition, GRI will get you there.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

www.gritires.com